

**CENG 465**  
**Spring 2010-2011**

**Assignment #1**  
**(Programming Assignment)**  
**SOLUTIONS**

**Question 1:** Describe your modification to the original NW algorithm.

Modified DP recurrence relations are as follows:

$$F(0,0) = 0$$

$$F(i,0) = \begin{cases} F(i-1,0) - 1 & \text{if flanking(seq1.i)} \\ F(i-1,0) - 3 & \text{if !flanking(seq1.i)} \end{cases}$$

$$F(0,j) = \begin{cases} F(0,j-1) - 1 & \text{if flanking(seq2.j)} \\ F(0,j-1) - 3 & \text{if !flanking(seq2.j)} \end{cases}$$

$$F(i,j) = \max \begin{cases} F(i,j-1) - 1 & \text{if (flanking(seq2.j))} \\ F(i,j-1) - 3 & \text{if (!flanking(seq2.j))} \\ F(i-1,j) - 1 & \text{if (flanking(seq1.i))} \\ F(i-1,j) - 3 & \text{if (!flanking(seq1.i))} \\ F(i-1,j-1) + s(seq1.i, seq2.j) \end{cases}$$

$$s(seq1.i, seq2.j) = \begin{cases} 7 & \text{if (seq1.i==seq2.j \&\& !flanking(seq1.j) \&\& !flanking(seq2.j))} \\ 4 & \text{if (seq1.i==seq2.j \&\& flanking(seq1.j) \&\& flanking(seq2.j))} \\ 2 & \text{if (seq1.i==seq2.j \&\& flanking(seq1.j) != flanking(seq2.j))} \\ -5 & \text{if (seq1.i != seq2.j \&\& !flanking(seq1.j) \&\& !flanking(seq2.j))} \\ -3 & \text{if (seq1.i != seq2.j \&\& flanking(seq1.j) \&\& flanking(seq2.j))} \\ -8 & \text{if (seq1.i != seq2.j \&\& flanking(seq1.j) != flanking(seq2.j))} \end{cases}$$

**Question 2:** Analyze the running time complexity of your program theoretically. Did the modifications to the original algorithm cause an increase in the running time? You may ignore constant time increases.

The modifications are constant time condition checks to check whether the current row or the current column is a flanking region when filling the table. So, the asymptotic time complexity in Big-Oh notation does not change. The solution is still  $O(mn)$ . However, these additional "if" statements will make it a little bit slower compared to the original version.

**Question 3:** What are the alignment scores for the 5 test sequence pairs?

The alignment scores are as follows:

test1.seq → 373  
test2.seq → 226  
test3.seq → 509  
test4.seq → 1780  
test5.seq → 272

**Question 4:** What are the alignments for the 5 test sequence pairs?

The alignments are provided in the output files test?.out

**Question 5:** For test5, i.e., the fifth test sequence pair, if the length of the flanking region was different, could you get a better alignment score? In other words, ignore the length provided in the test file and then find the best length of the flanking region which results in the maximum alignment score. There are  $\lfloor L/2 \rfloor - 1$  different lengths you should try if the length of the shorter sequence is  $L$  and any region has at least one nucleotide.

Yes, we could get a better score. For flanking length 3 and 4 an alignment of length 286 is possible.